(12) (19) (CA) Demande-Application



CIPO
CANADIAN INTELLECTUAL
PROPERTY OFFICE

(21) (A1) **2,251,096**

(86) 1998/02/12 (87) 1998/08/20

(72) LEVIN, Philip S., US

(72) SALTONSTALL, Jon, US

(72) NGUYEN, Loi, US

(72) ROSENSCHEIN, Uri, IL

(71) ANGIOSONICS INC., US

(51) Int.Cl. 6 A61B 17/36, A61B 17/22

(30) 1997/02/13 (60/038,180) US

(30) 1997/05/19 (08/858,247) US

(54) APPAREIL D'EMISSION D'ULTRASONS ET PROCEDE D'UTILISATION ASSOCIE

(54) ULTRASOUND TRANSMISSION APPARATUS AND METHOD OF USING SAME



(57) L'invention concerne un procédé et un système de traitement aux ultrasons de pathologies endovasculaires, comme des régions sténosées ou occluses de vaisseaux sanguins. Ce système de traitement aux ultrasons comprend une sonde ultrasonore présentant une extrémité proximale et une extrémité distale. On peut également utiliser un cathéter-guide et un fil-guide, et on peut coulisser la sonde dans la lumière intérieure du cathéter. La sonde peut présenter au niveau de son extrémité proximale une trompe, un élément de transmission, lequel présente une extrémité proximale et une extrémité distale et est relié à la trompe au niveau de son extrémité proximale, ainsi qu'un embout distal relié à l'extrémité distale de l'élément de transmission. Cet élément peut comporter un ou plusieurs fils de transmission, dotés d'extrémités proximales et distales, et reliés en série ou en parallèle.

(57) An ultrasonic treatment system and method for utilizing ultrasound to treat intravascular conditions, such as stenotic and occluded regions of blood vessels, are provided. The ultrasonic treatment system includes an ultrasonic probe (100), having a proximal and distal end. A guide catheter and guidewire may also be provided and the probe (100) can be slidably disposed within the guide catheter's inner lumen. The probe can include a horn (125) at the proximal end, a transmission member (B, C, D, E) with a proximal and a distal end connected to the horn at the transmission member proximal end (B), and a distal tip (150) connected at the transmission member's distal end. The transmission member may include one or more transmission wires (C, E), having proximal and distal ends connected serially or in parallel.

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent A61B 17/36	: Classification ⁶ :	A3	·	i) International Publication Number: 3) International Publication Date:	WO 98/35721 20 August 1998 (20.08.98)
		7) 1	US US	(81) Designated States: AL, AM, AT BY, CA, CH, CN, CU, CZ, E HU, ID, IL, IS, JP, KE, KG, K LT, LU, LV, MD, MG, MK, PT, RO, RU, SD, SE, SG, S UG, UZ, VN, YU, ARIPO pa SD, SZ, UG, ZW), Eurasian p MD, RU, TJ, TM), European ES, FI, FR, GB, GR, IE, IT, patent (BF, BJ, CF, CG, CI, SN, TD, TG).	DE, DK, EE, ES, FI, GB, GE, CP, KR, KZ, LC, LK, LR, LS, MN, MW, MX, NO, NZ, PL, L, SK, TJ, TM, TR, TT, UA, L, SK, TJ, TM, TR, TT, UA, L, SK, CH, GM, KE, LS, MW, attent (AM, AZ, BY, KG, KZ, patent (AT, BE, CH, DE, DK,
(72) Inventors: LEVIN, Philip, S.; 531 Thompson Road, Thompson, CT 06277 (US). SALTONSTALL, Jon; 58 Till Rock Lane, Norwell, MA 02061 (US). NGUYEN, Lai; 7-2 High Rock Way #2, Allston, MA 02134 (US). ROSENSCHEIN, Uri; Kfar Daniel, 73125 Israel (IL).			Published With international search report. (88) Date of publication of the interna	ational search report: 8 October 1998 (OS 10 98)	

(74) Agents: POKOTILOW, Steven, B. et al.; Stroock & Stroock & Lavan, 180 Maiden Lane, New York, NY 10038 (US).

8 October 1998 (08.10.98)

(54) Title: ULTRASOUND TRANSMISSION APPARATUS AND METHOD OF USING SAME



(57) Abstract

An ultrasonic treatment system and method for utilizing ultrasound to treat intravascular conditions, such as stenotic and occluded regions of blood vessels, are provided. The ultrasonic treatment system includes an ultrasonic probe (100), having a proximal and distal end. A guide catheter and guidewire may also be provided and the probe (100) can be slidably disposed within the guide catheter's inner lumen. The probe can include a horn (125) at the proximal end, a transmission member (B, C, D, E) with a proximal and a distal end connected to the hom at the transmission member proximal end (B), and a distal tip (150) connected at the transmission member's distal end. The transmission member may include one or more transmission wires (C, E), having proximal and distal ends connected scrially or in parallel.